

Package: hetu (via r-universe)

September 10, 2024

Type Package

Title Structural Handling of Finnish Personal Identity Codes

Version 1.0.7

Date 2022-05-20

MailingList rOpenGov <ropengov-forum@googlegroups.com>

Description Structural handling of Finnish identity codes (natural persons and organizations); extract information, check ID validity and diagnostics.

License BSD_2_clause + file LICENSE

VignetteBuilder knitr

Encoding UTF-8

BugReports <https://github.com/ropengov/hetu/issues>

URL <https://ropengov.github.io/hetu/>, <https://github.com/ropengov/hetu>

Depends R (>= 3.6.0)

Imports lubridate, checkmate, parallel

Suggests Cairo, knitr, testthat, rmarkdown, covr, dplyr

RoxygenNote 7.2.0

X-schema.org-isPartOf <http://ropengov.org/>

X-schema.org-keywords ropengov

Config/Needs/website magick, ropengov/rogtemplate

Repository <https://ropengov.r-universe.dev>

RemoteUrl <https://github.com/rOpenGov/hetu>

RemoteRef HEAD

RemoteSha 9d3c9b5e58677e816d8bf5329c7bc87e0a9cbe53

Contents

bid_ctrl	2
hetu	3
hetu_control_char	4
hetu_diagnostic	5
pin_age	6
pin_ctrl	7
pin_date	8
pin_sex	8
rbid	9
rpip	10
satu_control_char	11
satu_ctrl	12
Index	13

bid_ctrl	<i>Check Validity of Finnish Business ID (Y-tunnus)</i>
----------	---

Description

A function that checks whether a bid (Finnish Business ID) is valid. Returns TRUE or FALSE.

Usage

```
bid_ctrl(bid)
```

Arguments

bid a vector of 1 or more business identity numbers

Examples

```
bid_ctrl(c("0000000-0", "0000001-9")) # TRUE TRUE
bid_ctrl("0737546-1") # FALSE
```

 hetu *Generic Extraction Tool for Finnish Personal Identity Codes*

Description

Extract embedded information from Finnish personal identity codes (hetu).

Usage

```
hetu(pin, extract = NULL, allow.temp = FALSE, diagnostic = FALSE)
```

Arguments

pin	Finnish personal identity code(s) as a character vector
extract	Extract only selected part of the information. Valid values are "hetu", "sex", "p.num", "ctrl.char", "date", "day", "month", "year", "century", "is.temp". If NULL (default), returns all information.
allow.temp	Allow artificial or temporary PINs (personal numbers 900-999). If FALSE (default), only PINs intended for official use (personal numbers 002-899) are allowed.
diagnostic	Print additional information about possible problems in PINs. The checks are "valid.p.num", "valid.ctrl.char", "correct.ctrl.char", "valid.date", "valid.day", "valid.month", "valid.length", "valid.century". Default is FALSE which returns no diagnostic information.

Value

Finnish personal identity code data.frame, or if extract parameter is set, the requested part of the information as a vector. Returns an error or NA if the given character vector is not a valid Finnish personal identity code.

hetu	Finnish personal identity code as a character vector. A correct pin should be in the form DDMMYYCZZZQ, where DDMMYY stands for date, C for century sign, ZZZ for personal number and Q for control character.
sex	sex of the person as a character vector ("Male" or "Female").
p.num	Personal number part of the identity code.
ctrl.char	Control character for the personal identity code.
date	Birthdate.
day	Day of the birthdate.
month	Month of the birthdate.
year	Year of the birthdate.
century	Century character of the birthdate: + (1800), - (1900) or A (2000).
valid.pin	Does the personal identity code pass all validity checks: (TRUE or FALSE)

Author(s)

Pyry Kantanen, Jussi Paananen

See Also

[pin_ctrl](#) For validating Finnish personal identity codes.

Examples

```

hetu("111111-111C")
hetu("111111-111C")$date
hetu("111111-111C")$sex
# Same as previous, but using extract argument
hetu("111111-111C", extract="sex")
# Process a vector of hetu's
hetu(c("010101-0101", "111111-111C"))
# Process a vector of hetu's and extract sex information from each
hetu(c("010101-0101", "111111-111C"), extract="sex")

```

hetu_control_char	<i>Calculate Control Character for Personal Identity Code</i>
-------------------	---

Description

Calculate a valid control character for an incomplete Finnish personal identity codes (hetu).

Usage

```
hetu_control_char(pin, with.century = TRUE)
```

Arguments

pin	An incomplete PIN that ONLY has a date, century marker (optional, see parameter with.century) and personal number
with.century	If TRUE (default), the function assumes that the PIN input contains a century marker (DDMMYYQZZZ). If FALSE, the function assumes that the PIN contains only date and personal number (DDMMYYZZZ).

Details

This method of calculating the control character was devised by mathematician Erkki Pale (1962) to detect input errors but also to detect errors produced by early punch card machines. The long number produced by writing the birth date and the personal number together are divided by 31 and the remainder is used to look up the control character from a separate table containing alphanumeric characters except letters G, I, O, Q and Z.

The method of calculating the control character does not need century character and therefore the function has an option to omit it.

Value

Control character, either a number 0-9 or a letter.

Author(s)

Pyry Kantanen

See Also

[hetu](#) For extracting information from Finnish personal identity codes.

Examples

```
hetu_control_char("010101-010")  
hetu_control_char("010101010", with.century = FALSE)
```

hetu_diagnostic

Diagnostics Tool for Personal Identity Codes

Description

Prints information on the tests that are used to confirm or reject the validity of each personal identity code.

Usage

```
hetu_diagnostic(pin, extract = NULL)
```

```
pin_diagnostic(pin, extract = NULL)
```

Arguments

pin	Finnish personal identification number as a character vector, or vector of identification numbers as a character vectors
extract	Extract only selected part of the diagnostic information. Valid values are "hetu", "is.temp", "valid.p.num", "valid.ctrl.char", "correct.ctrl.char", "valid.date", "valid.day", "valid.month", "valid.length", "valid.century". If NULL (default), returns all information.

Value

A data.frame containing diagnostic checks about PINs.

See Also

[hetu](#) for the main function on which hetu_diagnostic relies on.

Examples

```

diagnosis_example <- c("010101-0102", "111111-111Q",
"010101B0101", "320101-0101", "011301-0101",
"010101-01010", "010101-0011")
## Print all diagnostics for various fake personal identity codes
hetu_diagnostic(diagnosis_example)
# Extract century-related checks
hetu_diagnostic(diagnosis_example, extract = "valid.century")
diagnosis_example <- c("010101-0102", "111111-111Q",
"010101B0101", "320101-0101", "011301-0101",
"010101-01010", "010101-0011")
## Print all diagnoses
pin_diagnostic(diagnosis_example)

```

pin_age

Extract Age from Personal Identity Code

Description

Calculate age in years, months, weeks or days from personal identity codes.

Usage

```
pin_age(pin, date = Sys.Date(), timespan = "years", allow.temp = FALSE)
```

```
hetu_age(pin, date = Sys.Date(), timespan = "years", allow.temp = FALSE)
```

Arguments

pin	Finnish personal identity code(s) as a character vector
date	Date at which age is calculated. If a vector is provided it must be of the same length as the pin argument.
timespan	Timespan to use to calculate age. The possible timespans are: <ul style="list-style-type: none"> • years (Default) • months • weeks • days
allow.temp	Allow artificial or temporary PINs (personal numbers 900-999). If FALSE (default), only PINs intended for official use (personal numbers 002-899) are allowed.

Value

Age as an integer vector.

Examples

```
ex_pin <- c("010101-0101", "111111-111C")
pin_age(ex_pin, date = "2012-01-01")
```

```
ex_pin <- c("010101-0101", "111111-111C")
hetu_age(ex_pin, date = "2012-01-01")
```

pin_ctrl

Check Validity of Personal Identity Code

Description

Validate Finnish personal identity codes (hetu).

Usage

```
pin_ctrl(pin, allow.temp = FALSE)
```

```
hetu_ctrl(pin, allow.temp = FALSE)
```

Arguments

pin	Finnish personal identity code(s) as a character vector
allow.temp	If TRUE, temporary PINs (personal numbers 900-999) are handled similarly to regular PINs (personal numbers 002-899), meaning that otherwise valid temporary PIN will return a TRUE. Default is FALSE.

Value

A logical vector indicating whether the input vector contains valid Finnish personal identity codes.

Author(s)

Pyry Kantanen

See Also

[hetu](#) For extracting information from Finnish personal identity codes.

Examples

```
pin_ctrl("010101-0101") # TRUE
pin_ctrl("010101-010A") # FALSE
pin_ctrl(c("010101-0101", "010101-010A")) # TRUE FALSE
hetu_ctrl("010101-0101") # TRUE
hetu_ctrl("010101-010A") # FALSE
hetu_ctrl(c("010101-0101", "010101-010A")) # TRUE FALSE
```

pin_date	<i>Extract Date of Birth from Personal Identity Code</i>
----------	--

Description

Returns the date of birth in date format.

Usage

```
pin_date(pin, allow.temp = FALSE)
```

```
hetu_date(pin, allow.temp = FALSE)
```

Arguments

pin	Finnish personal identity code(s) as a character vector
allow.temp	Allow artificial or temporary PINs (personal numbers 900-999). If FALSE (default), only PINs intended for official use (personal numbers 002-899) are allowed.

Value

Date of birth as a vector in date format.

Examples

```
pin_date(c("010101-0101", "111111-111C"))
```

```
hetu_date(c("010101-0101", "111111-111C"))
```

pin_sex	<i>Extract Sex from Personal Identity Code</i>
---------	--

Description

Extract sex (as binary) from Finnish personal identification code.

Usage

```
pin_sex(pin, allow.temp = TRUE)
```

```
hetu_sex(pin, allow.temp = TRUE)
```


Arguments

`pin` Finnish personal identity code(s) as a character vector

`allow.temp` Allow artificial or temporary PINs (personal numbers 900-999). If FALSE (default), only PINs intended for official use (personal numbers 002-899) are allowed.

Value

Factor with label 'Male' and 'Female'.

Author(s)

Pyry Kantanen, Leo Lahti

See Also

[hetu](#) For general information extraction

Examples

```
pin_sex("010101-010A")
hetu_sex("010101-010A")
```

`rbid`*Generate Random Finnish Business ID's (Y-tunnus)*

Description

A function that generates random Finnish Business ID's, bid-numbers (Y-tunnus).

Usage

```
rbid(n)
```

Arguments

`n` number of generated BIDs

Value

a vector of generated BID-numbers.

Examples

```
x <- rbid(3)
bid_ctrl(x)
```

`rpin`*Generate Random Personal Identity Codes*

Description

A function that generates random Finnish personal identity codes (hetu codes).

Usage

```
rpin(  
  n,  
  start.date = as.Date("1895-01-01"),  
  end.date = Sys.Date(),  
  p.male = 0.4,  
  p.temp = 0,  
  num.cores = 1  
)
```

```
rhetu(  
  n,  
  start.date = as.Date("1895-01-01"),  
  end.date = Sys.Date(),  
  p.male = 0.4,  
  p.temp = 0,  
  num.cores = 1  
)
```

Arguments

<code>n</code>	number of generated hetu-pins
<code>start.date</code>	Lower limit of generated hetu dates, character string in ISO 8601 standard, for example "2001-02-03". Default is "1895-01-01".
<code>end.date</code>	Upper limit of generated hetu. Default is current date.
<code>p.male</code>	Probability of males, between 0.0 and 1.0. Default is 0.4.
<code>p.temp</code>	Probability of temporary identification numbers, between 0.0 and 1.0. Default is 0.0.
<code>num.cores</code>	The number of cores for parallel processing. The number of available cores can be determined with <code>detectCores()</code> . Default is 1.

Details

There is a finite number of valid personal identity codes available per day. More specifically, there are 498 odd personal numbers for males and 498 even personal numbers for females from range 002-899. Additionally there are 50 odd numbers for males and 50 even numbers for females in the temporary personal identity code number range 900-999 that is not normally in use. This function

will return an error "too few positive probabilities" in `sample.int` function if you try to generate too many codes in a short enough timeframe.

The theoretical upper limit of valid PINs is in the millions since there are 898 PINs available for each day, 327770 for each year. In practice this number is much lower since same personal number component cannot be "recycled" if it has been used in the past. To illustrate, if an identity code "010101-0101" has already been assigned to someone born in 1901-01-01, a similar code "010101A0101" for someone born in 2001-01-01 could not be used.

Value

a vector of generated hetu-pins.

Author(s)

Pyry Kantanen, Jussi Paananen

Examples

```
x <- rpin(3)
hetu(x)
hetu(x, extract = "sex")
hetu(x, extract = "ctrl.char")

x <- rhetu(3)
x
```

satu_control_char *Finnish Unique Identification Number Control Character Calculator*

Description

Calculate a valid control character for an incomplete Finnish Unique Identification Number (FINUID, or sähköinen asiointitunnus SATU).

Usage

```
satu_control_char(pin, print.full = FALSE)
```

Arguments

<code>pin</code>	An incomplete FINUID that has 8 first numbers.
<code>print.full</code>	Should the function print only the whole FINUID-number (TRUE) or only the control character (FALSE). Default is FALSE.

Details

This method of calculating the control character was devised by mathematician Erkki Pale (1962) to detect input errors but also to detect errors produced by early punch card machines. The long number produced by writing the birth date and the personal number together are divided by 31 and the remainder is used to look up the control character from a separate table containing alphanumeric characters except letters G, I, O, Q and Z.

The method of calculating the control character does not need century character and therefore the function has an option to omit it.

Value

Control character, either a number 0-9 or a letter (length 1 character). If parameter `print.full` is set to `TRUE`, the function returns a complete FINUID / SATU number (length 9 characters).

Author(s)

Pyry Kantanen

See Also

For more detailed information about FINUID, see Finnish Digital and population data services agency website: <https://dvv.fi/en/citizen-certificate-and-electronic-identity>

Examples

```
# The first assigned FINUID number, 10000001N.
satu_control_char("10000001")
```

satu_ctrl

Check Validity of Finnish Unique Identification Number (SATU)

Description

A function that checks whether a satu (Finnish Unique Identification Number) is valid. Returns `TRUE` or `FALSE`.

Usage

```
satu_ctrl(satu)
```

Arguments

`satu` a vector of 1 or more Unique Identification Numbers

Examples

```
satu_ctrl("10000001N") # TRUE
satu_ctrl(c("10000001N", "20000001B")) # TRUE FALSE
```

Index

bid_ctrl, 2

hetu, 3, 5, 7, 9

hetu_age (pin_age), 6

hetu_control_char, 4

hetu_ctrl (pin_ctrl), 7

hetu_date (pin_date), 8

hetu_diagnostic, 5

hetu_sex (pin_sex), 8

pin_age, 6

pin_ctrl, 4, 7

pin_date, 8

pin_diagnostic (hetu_diagnostic), 5

pin_sex, 8

rbid, 9

rhetu (rpin), 10

rpin, 10

satu_control_char, 11

satu_ctrl, 12